

TAMKO® NO.30 Asphalt Saturated Organic Felt

PRODUCT DATA

Manufactured in Joplin, MO, Phillipsburg, KS, Frederick, MD, Tuscaloosa, AL, and Green Cove Springs, FL



TAMKO® NO. 30 SATURATED FELT features a tough TAMKO organic felt (non-perforated) that is saturated with asphalt.

USES


Accepted for use as an underlayment felt to be applied over the deck prior to the installation of TAMKO asphalt shingles.

CERTIFICATIONS

U.L. Prepared Roofing Accessory

PRODUCT DATA*

Roll Dimensions	72' X 36"
Coverage per roll	2 Squares
Laying Lines	2", 4", 17"



*All values stated as nominal

THIS PRODUCT IS SOLD "AS IS" WITHOUT WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



CAUTION: The National Institute for Occupational Safety and Health (NIOSH) has concluded that fumes of heated asphalt are a potential occupational carcinogen. Do not heat or burn this product.

TAMKO®

BUILDING PRODUCTS

TAMKO Logo, Roofer Logo, and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

04/2008

Central District	220 West 4th St., Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr., Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St., Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp., Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave., Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.